

Rust Check Corporation
6175 Danville Road, Mississauga
Ontario, Canada L5T 2H7
PHONE: (905) 670-5411

PRODUCT: RUST CHECK 11010 BLACK ASPHALT UNDERCOATING AEROSOL 510G**Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

MANUFACTURER Rust Check Corporation
6175 Danville Road, Mississauga
Ontario, Canada L5T 2H7
PHONE: (905) 670-5411
CANUTEC EMERGENCY #:1-613-996-6666(24HR)

PRODUCT NAME..... RC11010 (Code: 11010) BLACK ASPHALT UNDERCOATING AEROSOL, 510G
CHEMICAL FAMILY..... ORGANIC COATING.
MOLECULAR WEIGHT..... NOT APPLICABLE.
CHEMICAL FORMULA..... NOT APPLICABLE.
TRADE NAMES & SYNONYMS..... NOT APPLICABLE
PRODUCT USES..... COATING, AEROSOL, AUTOMOTIVE USE
CAS #..... NOT APPLICABLE.

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
PETROLEUM DISTILLATES (STODDARD SOLVENT)	10-30	100 ppm	8052-41-3	5 g/kg ORAL-RAT	5500 mg/m3 INHAL-RAT
MINERAL SPIRITS	10-30	100 ppm	64742-47-8	>5000 mg/kg ORAL - RAT	1400 ppm/4H INHAL - RAT
VM&P NAPHTHA	5-10	300 ppm	64742-89-8	NOT AVAILABLE	3400 ppm (4 hr) INHAL - RAT
ISOBUTANE	10-30	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	1-5	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.
INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.

EYE CONTACT..... MAY CAUSE IRRITATION.
SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.
SKIN CONTACT..... MAY CAUSE IRRITATION.
EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.
EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS
EXPOSURE LIMIT OF MATERIAL..... SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... >245.
SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.

FLAMMABILITY..... EXTREMELY FLAMMABLE.
IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
FLASH POINT (C), TAG CLOSED CUP..... 9.
UPPER FLAMMABLE LIMIT..... 6.
(% BY VOLUME)
LOWER FLAMMABLE LIMIT..... 0.9.
(% BY VOLUME)
EXPLOSION DATA
SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.
SENSITIVITY TO IMPACT..... NOT APPLICABLE.
HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.

PRODUCT: RUST CHECK 11010 BLACK ASPHALT UNDERCOATING AEROSOL 510G**Section 05: FIRE FIGHTING MEASURES**

AEROSOL FLAME PROJECTION
CLASSIFIED AS:..... >15cm BUT <100cm.

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
EYE/TYPE..... SAFETY GLASSES.
FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
APPEARANCE..... BLACK.
ODOR..... HYDROCARBON.
ODOR THRESHOLD..... NOT AVAILABLE.
VAPOUR PRESSURE(PSIG)-AEROSOL..... 35-50.
@ 20 C
EVAPORATION RATE..... GREATER THAN 1.
n-BUTYL ACETATE = 1
VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
(BY WEIGHT)
(BY WEIGHT)
SOLUBILITY IN WATER g/L (20°C)..... NEGLIGIBLE.
pH..... NOT APPLICABLE.
SPECIFIC GRAVITY (LIQUID)..... 0.94-0.98.
COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
SPECIFIC GRAVITY (AEROSOL)..... 0.80-0.84.
FREEZING POINT: (°C)..... NOT AVAILABLE.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
CHEMICAL STABILITY:
YES..... UNDER NORMAL CONDITIONS.
NO, WHICH CONDITIONS?..... NOT APPLICABLE.
COMPATIBILITY WITH OTHER SUBSTANCES:
NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
REACTIVITY CONDITIONS?..... NOT APPLICABLE.
HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... BENZENE - CAUSES FOETOTOXICITY IN ANIMALS AT DOSES WHICH ARE MATERNALLY TOXIC. DOES NOT IMPAIR FERTILITY.
IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.
CARCINOGENICITY OF MATERIAL..... ALIPHATIC PETROLEUM DISTALLATES CONTAINS TRACE AMOUNT OF BENZENE - CARCINOGENIC RISKS TO HUMANS BASED ON THE EVALUATION OF IARC WORKING GROUP (SEE SECTION 02).
TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.
MUTAGENICITY..... BENZENE - MAY CAUSE HERITABLE GENETIC DAMAGE.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

PRODUCT: RUST CHECK 11010 BLACK ASPHALT UNDERCOATING AEROSOL 510G**Section 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY(AEROSOLS, UN1950, CLASS 2.1) .
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION**CANADIAN REGULATIONS:**

WHMIS CLASSIFICATION..... A,B2,D2B.
CNFC SECTION 3.3.5..... LEVEL 3.
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.
HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.
HMIS RATING PERSONAL PROTECTION..... B.
NFPA CODE 30B..... LEVEL 3.
SARA 313 INFORMATION:..... THIS PRODUCT CONTAINS NO INGREDIENTS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372.
CAS #: CHEMICAL NAME:
N/A.
CALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.
CAS #: CHEMICAL NAME:
*71-43-2 BENZENE (TRACE AMOUNT IN MINERAL SPIRITS).
TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.
VOC (w/w%)..... 60-64.

Section 16: OTHER INFORMATION

NOTICE FROM RUST CHECK CORP..... THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY RUST CHECK CORPORATION FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. RUST CHECK CORP ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES
PREPARATION DATE March 25, 2016