

RUST CHECK CORPORATION
6175 Danville Road, Mississauga
ONTARIO, CANADA L5T 2H7

PRODUCT: RUST CHECK RUST PAINT - GLOSS BLACK #21425 340G**Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

MANUFACTURERRUST CHECK CORPORATION
6175 Danville Road, Mississauga
ONTARIO, CANADA L5T 2H7

PRODUCT NAME.....CANUTEC EMERGENCY #:1-613-996-6666(24HR)
RUST CHECK RUST PAINT - GLOSS BLACK #21425 (340G)

CHEMICAL FAMILY.....ALKYD BASED COATING.

MOLECULAR WEIGHT.....NOT APPLICABLE.

CHEMICAL FORMULA.....MIXTURE.

TRADE NAMES & SYNONYMS.....NOT APPLICABLE

PRODUCT USES.....SPRAY PAINT.

CAS #.....NOT APPLICABLE

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ACETONE	15-40	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
XYLENE	7-13	100 ppm	1330-20-7	4.3 g/kg ORAL - RAT	6350 ppm (4 hr) INHAL - RAT
ETHYLBENZENE	1-5	100 ppm	100-41-4	5460 mg/kg ORAL-RAT	NOT AVAILABLE
TOLUENE	7-13	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
PROPYLENE GLYCOL METHYL ETHER ACETATE	1-5	N/E	108-65-6	8500 mg/kg ORAL - RAT	>4345 ppm (6 hr) INHAL - RAT
METHYL ISOBUTYL KETONE	1-5	50 ppm	108-10-1	2080 mg/kg ORAL - RAT	2000 ppm (4 hr) INHAL - RAT
CARBON BLACK	0.1-1.0	3.5 mg/m3	1333-86-4	>10000 mg/kg ORAL - RAT	NOT AVAILABLE
ISOBUTANE	5-10	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

INGESTION.....MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.

INHALATION.....INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXIANT.

EYE CONTACT.....MAY CAUSE IRRITATION.

SKIN ABSORPTION.....NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.

SKIN CONTACT.....MAY CAUSE IRRITATION.

EFFECTS OF ACUTE EXPOSURE.....DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.

EFFECTS OF CHRONIC EXPOSURE.....SOLVENTS MAY CAUSE DEFATTING DERMATITIS

EXPOSURE LIMIT OF MATERIAL.....SEE SECTION 2.

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C).....272-527.

SPECIAL PROCEDURES.....WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.

FLAMMABILITY.....EXTREMELY FLAMMABLE.

IF YES, UNDER WHICH CONDITIONS?.....EXCESSIVE HEAT, SPARKS AND OPEN FLAME.

EXTINGUISHING MEDIA.....WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

UPPER FLAMMABLE LIMIT.....15.1.

(% BY VOLUME)

LOWER FLAMMABLE LIMIT.....1.

PRODUCT: RUST CHECK RUST PAINT - GLOSS BLACK #21425 340G**Section 05: FIRE FIGHTING MEASURES**

(% BY VOLUME)
 EXPLOSION DATA
 SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.
 SENSITIVITY TO IMPACT..... NOT APPLICABLE.
 HAZARDOUS COMBUSTION
 PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
 AEROSOL FLAME PROJECTION
 CLASSIFIED AS:..... >15cm BUT <100cm.
 FLASHBACK..... NONE.
 FLASH POINT(°C),TAG CLOSED-CUP LOWEST KNOWN VALUE IS ACETONE @-18C.
 (CONCENTRATE)

Section 06: ACCIDENTAL RELEASE MEASURES

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
 HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
 EYE/TYPE..... SAFETY GLASSES.
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
 OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... BLACK.
 ODOR..... KETONE.
 ODOR THRESHOLD..... NOT AVAILABLE.
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 55 - 65.
 @ 20 C
 BOILING POINT (°C)(CONC)..... 57 - 150.
 EVAPORATION RATE..... GREATER THAN 1.
 n-BUTYL ACETATE = 1
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
 (BY WEIGHT)
 SOLUBILITY IN WATER g/L (20°C)..... NEGLIGIBLE.
 pH..... NOT APPLICABLE.
 SPECIFIC GRAVITY (LIQUID)..... 0.84-0.88.
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
 FREEZING POINT: (°C)..... NOT AVAILABLE.
 AEROSOL PERCENT VOLATILE..... 88-89.
 (BY WEIGHT).
 SPECIFIC GRAVITY (AEROSOL)..... 0.73-0.77.
 AEROSOL PERCENT VOC (w/w)..... 52-53.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF
 DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
 CHEMICAL STABILITY:
 YES..... UNDER NORMAL CONDITIONS.
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.
 COMPATIBILITY WITH OTHER SUBSTANCES:
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... XYLENE - HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT LEVELS TOXIC TO THE MOTHER, AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.
 TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE ADVERSE FETAL DEVELOPMENTAL EFFECTS.
 IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
 SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.

PRODUCT: RUST CHECK RUST PAINT - GLOSS BLACK #21425 340G**Section 11: TOXICOLOGICAL INFORMATION**

CARCINOGENICITY/MUTAGENICITY..... XYLENE - THIS PRODUCT CONTAINS ETHYLBENZENE (ETHYLBENZENE IS IN XYLENE). ETHYLBENZENE HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS. TOXICITY TESTS CARRIED OUT FOR CHRONIC EFFECTS AND MUTAGENICITY HAVE BEEN NEGATIVE. THE RELEVANCE OF THIS FINDING TO HUMANS IS UNCERTAIN. IARC HAS CLASSIFIED ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN.

CARCINOGENICITY OF MATERIAL..... CONTAINS TRACE AMOUNT OF CARBON BLACK CLASSIFIED AS POSSIBLE CARCINOGEN FOR HUMAN BEINGS (2B) BY IARC AS RESPIRABLE DUST. CARBON BLACK BEING WET IN THE PRODUCT, THE RISK OF INHALING CAN ARISE ONLY DURING SANDING OR SPRAYING.

TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

Section 14: TRANSPORTATION INFORMATION

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY (AEROSOLS, UN1950, CLASS 2.1) .

D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION**CANADIAN REGULATIONS:**

WHMIS CLASSIFICATION..... A,B5,D2A,D2B.

CNFC SECTION 3.3.5..... LEVEL 2.

CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.

HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.

HMIS RATING REACTIVITY..... 1 SLIGHT HAZARD.

HMIS RATING PERSONAL PROTECTION..... B.

NFPA CODE 30B..... LEVEL 2.

SARA 313 INFORMATION: THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CAS #:	CHEMICAL NAME:
*108-88-3	TOLUENE
*1330-20-7	XYLENE
*100-41-4	ETHYL BENZENE

CALIFORNIA PROPOSITION 65:..... THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CAS #:	CHEMICAL NAME:
*108-88-3	TOLUENE
*100-41-4	ETHYL BENZENE IN XYLENE
*1333-86-4	CARBON BLACK

TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.

VOC (w/w%)..... 52-53.

Section 16: OTHER INFORMATION

NOTICE FROM KG PACKAGING INC THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY K-G PACKAGING INC. FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. K-G PACKAGING INC. ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.

PREPARED BY..... TECHNICAL SERVICES

PREPARATION DATE June 1, 2016